




**Dye Sublimation Paper Printer** 

Techway Technology (International) Ltd Room 302, Sunbeam Centre, 27 Shing Yip Street, Kwun Tong, Hong Kong

香港九龍觀塘成業街27號日昇中心302室 Tel: +852 2317 7270 / Fax: +852 2317 7227

email: info@techwaytechnology.com www.techwaytechnology.com







Ink on-line processing (filtration and degasification) come true. Print fluently, province paper and Ink with high efficiency and low cost.

Configure a large capacity ink system with low ink alarm (15L/color). Reduce the ink filling times and ensure the ink supply more stable.

Automatic constant tension feeding and take up paper system, paper roll using air shalf roller, can carry 500 meters long paper (thickness >=5g), decrease the times of operation, greatly improve accuracy and the efficiency.

Low power built-In dryer for roll-to-roll paper take up, drying at the bottom and preposition realize high thermal efficiency, energy conservation, environmental protection, and thorough dry.

## FEATURES & SPECIFICATIONS

- 1. Print head
- 2. No. of printhead
- 3. Material type (Width)
- 4. Material type (Thickness)
- 5. Material type (Diameter)
- 6. Material weight (Core diameter)
- 7. Printing wdth
- 8. Size (Printer)
- 9. Net Weight
- 10. Vollage

VSD Pizeo (400 nozzles x 8 lines)

4 nos.

≤1925mm

≤**2.0**mm

≤300mm

≤60kg

Max. 1915mm

3210x1220x1560mm

466kg

AC220V / 15A / 50/60Hz

## MATERIAL TYPE

Width

<=1925mm

**Thickness** 

<=300mm

**Diameter** 

<=60kg

## PRODUCTION SPEED

2 pass

150 m<sup>2</sup>/h

3 pass

100 m<sup>2</sup>/h

4 pass

75 m<sup>2</sup>/h

**PC** requirement

Ink on-line processing

Ink system

Take up paper system

Heater